D425ML

Technical Specifications

42” Metal Frame

- 42” Metal Frame
- Resolution 1920 x 1080
- Brightness 500cd/㎡
- Contrast Ratio 800:1

Display Panel	Screen Size		**42”**
	Active Display Area (mm)		**930.3 x 523.0**
	Aspect Ratio		**1920 x 1080 (WUXGA)**
	Display Colors		**16 : 9**
	Brightness (cd/㎡)(typ)		**500**
	Contrast Ratio		**800 : 1**
	Viewing angle (Hº/Vº)		**178º / 178º**
	Bezel Size (U/D/L/R)(mm)		**22.5 / 22.5 / 22 / 22**
	Outline Dimension (mm)		**983 x 576 x 51**
	Weight (kg)		**11.5**
	Life Time		**50,000h**
Resolution	Monitor		**1920 x 1080**
	DTV		**1080p**
Connectivity & Control	Input		**VGA (15pin D-sub), HDMI, Composite(BNC), Component(BNC), PC Audio, Composite Audio, Component Audio, RS232C**
	Output		**VGA (15pin D-sub), DVI (Connected type HDMI) -> HDMI (HDCP Not Supported), Composite(BNC), Component(BNC), RS232C, Speaker(Ready)**
	Multi-Screen Function (Loop)		**HDMI, VGA (15pin D-Sub), Component(BNC), Composite (BNC)**
	Power Requirement	Input Voltage	**100 - 240VAC**
		Consumption (typ)(W)	**220**
	Auto Cooling System		**Yes (1EA)**
	Auto Power Control (DPMS)		**Yes**
Feature	Option	AR Coating	**Option**
		Tempered Glass	**Option**
		Optical Bonding	**Option**
		Touch Screen	**Option**
		Transflective	**Option**
		Auto Brightness Control	**Option**
Mechanical	Dimension (mm)	Set (W x H x L)(mm)	**987.4 x 580.4 x 120.4**
		Bezel Size (U/D/L/R) (mm)	**27.2 / 27.2 / 27.2 / 27.2**
		Packed (W x H x L)(mm)	**1122 x 732 x 260**
	Weight (kg)	Set / Packed (kg)	**32kg / 36.5kg**
	Wall Mounting Hole (W x H)(mm)		**600 x 200**
Approvals	EMI / EMC		**FCC, CE, VCCI, KCC**
	Safety		**CB, TUV, cTUVus**
Accessories			**Power Cord, HDMI Cable (Option : DVI to HDMI / D-SUB / RS-232C / Audio Cable)**
OSD Language			**10 Language**
Temperature			**0℃ - 40℃**
Humidity			**20% - 80%**

HYUNDAI
HYUNDAI IT CORP.